

### IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A tool control system comprising:  
a pneumatic source;  
a vacuum source;  
a control mechanism coupled to the pneumatic source, to the vacuum source, to a supply hose, and to a pilot hose, wherein the supply hose and the pilot hose are to couple to a tool, wherein the control mechanism is to provide vacuum to the supply hose when air within the pilot hose has less than a predetermined pressure, and wherein the control mechanism is to provide air pressure to the supply hose when air within the pilot hose has greater than the predetermined pressure, and wherein the control mechanism includes  
a limit valve coupled to the pneumatic source and to the pilot hose, and  
a reversing valve coupled to the limit valve, to the vacuum source, to the pneumatic source, and to the supply hose.
2. (Canceled)
3. (Currently Amended) The tool control system recited in claim 1 [[2]], wherein the limit valve is to couple the reversing valve to the vacuum source when air within the pilot hose has less than the predetermined pressure, and wherein the limit valve is to couple the reversing valve to the pneumatic source when air within the pilot hose has greater than the predetermined pressure.

4. (Currently Amended) A system comprising:
- an air source;
  - a vacuum source; [[and]]
  - a control mechanism coupled to the air source and to the vacuum source, wherein the air source and the vacuum source are to couple to a tool comprising a first operator-depressible actuation element and a second operator-depressible actuation element, wherein the control mechanism is to provide vacuum to the tool when fewer than both actuation elements are actuated, ~~and~~ wherein the control mechanism is to provide air pressure to the tool when both actuation elements are actuated, and wherein the control mechanism includes
    - a limit valve coupled to the air source and to the pilot hose, and
    - a reversing valve coupled to the limit valve, to the vacuum source, to the air source, and to the supply hose;
    - and wherein the system further includes
    - a supply hose selectively coupleable to the air source or to the vacuum source; and
    - a pilot hose coupled to the first and second actuation elements,
    - wherein the supply hose and the pilot hose are to couple to the tool.
5. (Canceled)
6. (Currently Amended) The system recited in claim 4 [[5]], wherein the control mechanism is to provide vacuum to the supply hose when air within the pilot hose has less than a predetermined pressure, and wherein the control mechanism is to provide air pressure to the supply hose when air within the pilot hose has greater than the predetermined pressure.
- 7 (Canceled)
8. (Currently Amended) The system recited in claim 4 [[7]], wherein the limit valve is to couple the reversing valve to the vacuum source when air within the pilot hose has less than the predetermined pressure, and wherein the limit valve is to couple the reversing valve to the air source when air within the pilot hose has greater than the predetermined pressure.

9. (Currently Amended) A system comprising:
- an air source;
  - a vacuum source;
  - a control mechanism coupled to the air source and to the vacuum source, wherein the control mechanism is to couple to a tool comprising a first operator-actuatable actuation element and a second operator-actuatable actuation element, wherein the control mechanism includes
    - a limit valve coupled to the air source and to the pilot hose, and
    - a reversing valve coupled to the limit valve, to the vacuum source, to the air source, and to the supply hose; [[and]]
    - and wherein the system further includes
      - a pilot hose coupled to the control mechanism, wherein air within the pilot hose has less than a predetermined pressure when fewer than both actuation elements are actuated, and wherein air within the pilot hose has greater than a predetermined pressure when both actuation elements are actuated; and
      - a supply hose selectively coupleable to the air source or to the vacuum source;
      - wherein the supply hose and the pilot hose are to couple to the tool
10. (Canceled)
11. (Currently Amended) The system recited in claim 9 [[10]], wherein the control mechanism is to provide vacuum to the supply hose when air within the pilot hose has less than a predetermined pressure, and wherein the control mechanism is to provide air pressure to the supply hose when air within the pilot hose has greater than the predetermined pressure.
12. (Canceled)
13. (Currently Amended) The system recited in claim 9 [[12]], wherein the limit valve is to couple the reversing valve to the vacuum source when air within the pilot hose has less than the

**AMENDMENT UNDER 37 C.F.R. 1.116 – EXPEDITED PROCEDURE**

Serial Number: 10/655,822

Filing Date: September 5, 2003

Title: FASTENER INSTALLATION SYSTEMS (As Amended)

Assignee: Intel Corporation

---

**Page 5**

Dkt: 884.413US3 (INTEL)

predetermined pressure, and wherein the limit valve is to couple the reversing valve to the air source when air within the pilot hose has greater than the predetermined pressure.

14-20. (Canceled)